

GAS FIREPLACE INSERTS WITH STANDARD FIREPLACE - INDIVIDUELL



GAS FIREPLACE INSERT INDIVIDUELL 600 FRONT





GAS FIREPLACE INSERT
INDIVIDUELL 500
TUNNEL

6. GAS FIREPLACE INSERTS WITH STANDARD FIREPLACE - FRONT

GAS FIREPLACE INSERTS WITH STANDARD FIREPLACE - FRONT - Natural gas/LPG



DESCRIPTION	MODEL/AIR EXHAUST SYSTEM/DIMENSIONS	NATURAL GAS/LPG OPTIONAL	PRODUCT-NUMBER	POSSIBLE ACCESSORIES	
<p>GAS FIREPLACE INSERTS - INDIVIDUELL front - closed, length of the burner: individually, Air-exhaust system (exhaust \varnothing130 mm, combustion air \varnothing200 mm)</p> <p>Power: Natural gas or LPG: individually</p> <p>Including: Gas fireplace insert incl. decor wood and remote control</p> <p>Optional: 1 burner line of 2 can be switched off, Cool Down with gravity support, fan-assisted air recirculation</p>	<p>GAP-OT-300-400/40-F-G - INDIVIDUELL with AIR EXHAUST SYSTEM: \varnothing130/200 mm Sichtfenster wahlweise ca. 300-400 x 40 cm</p>  <p style="text-align: center;">Symbolbild</p>	<p>GAP-GAS viewing window approx. 300-400 x 40 cm</p>	GAP-OT-300-400/40-F-G	<p>decor stones lava broken (10 kg), decor stones Nero Marquina (10 kg), Superglow, power supply - control unit, smart relaisbox incl. interface, WIFI-control incl. modem and app, wall switch, emergency shutdown for gas appliances, control incl. receiver RW, gas socket (natural gas), small bottle egulator for gas bottle (LPG)</p>	
		<p>1 burner line of 2 can be switched off</p>	GAP-OT-300-400/40-F-G-BA		
		<p>Cool Down with gravity support</p>	GAP-OT-300-400/40-F-G-CODO		
		<p>fan-assisted air recirculation</p>	GAP-OT-300-400/40-F-G-VA		
		<p>Fan-Flex-Flue</p>	GAP-OT-300-400/40-F-G-FFFSET		
		<p>GAP-OT-500-600/40-F-G - INDIVIDUELL with AIR EXHAUST SYSTEM: \varnothing130/200 mm Sichtfenster wahlweise ca. 500-600 x 40 cm</p>  <p style="text-align: center;">Symbolbild</p>	<p>GAP-GAS viewing window approx. 500-600 x 40 cm</p>		GAP-OT-500-600/40-F-G
		<p>1 burner line of 2 can be switched off</p>	GAP-OT-500-600/40-F-G-BA		
		<p>Cool Down with gravity support</p>	GAP-OT-500-600/40-F-G-CODO		
		<p>fan-assisted air recirculation</p>	GAP-OT-500-600/40-F-G-VA		
		<p>Fan-Flex-Flue</p>	GAP-OT-500-600/40-F-G-FFFSET		
		<p>GAP-OT-700/40-F-G - INDIVIDUELL with AIR EXHAUST SYSTEM: \varnothing130/200 mm Sichtfenster wahlweise ca. 700 x 40 cm</p>  <p style="text-align: center;">Symbolbild</p>	<p>GAP-GAS viewing window approx. 700 x 40 cm</p>		GAP-OT-700/40-F-G
		<p>1 burner line of 2 can be switched off</p>	GAP-OT-700/40-F-G-BA		
	<p>Cool Down with gravity support</p>	GAP-OT-700/40-F-G-CODO			
	<p>fan-assisted air recirculation</p>	GAP-OT-700/40-F-G-VA			
	<p>Fan-Flex-Flue</p>	GAP-OT-700/40-F-G-FFFSET			
	CONTROL INCL. RECEIVER RW		FFERW		

